



www.ipnmessaging.com

CLIENT MANAGEMENT APOLLO A02 PADDLE PAGER

Perfect for Health Care Facilities, Restaurants, Churches and anywhere your customers are waiting for service. Give them the ability to travel your facility, campus or surrounding area. Let them shop, eat and explore while they wait. Waiting is not something your patients and clients suffer gladly. IPN's Client Management Paddle pagers can help your staff manage your waiting rooms efficiently and give them more time to work with your clients.



DISPLAY

- When you are paged, the LED buzzes, beeps or vibrates with red light

INDICATOR/ALERT

- Choice of Alerts: You can choose between different modes of alerts: vibrate, beep and blink.
- Page Alerts: When you receive a page, vibration, beep or LED blink alerts can work at the same time. You can also choose between one or two of the three different modes of alerts at the same time. 4 addresses are available and each can be programmed with unique alerts. The length of the alert is programmable as well.
- Out of Range indicator: The orange LED will blink when the pager is out of range (optional).
- Low Battery Indicator: When battery power reaches a low level, the orange LED is always on, prompting you to charge the battery.

RACK CHARGER

- Each charger can charge up to 10 paddles
- Each charger can be extended with multiplication. One adapter can be used for up to 4 desk chargers.
- Ni-MH rechargeable battery



FEATURES

- Standard business-card-size advertising area
- Battery life approximately 7 days on a single charge
- One-piece paddle style construction
- Shock-resistant casing
- Synthesized or crystal type
- Over the air "off"
- Available in all bands, VHF, UHF, 900 POCSAG synthesized

1-800-INDIANA (463-4262)

LaPorte | 6745 W. Johnson Road, LaPorte, IN 46350
Indianapolis | 3311 Shelby Street, Indianapolis, IN 46227

CLIENT MANAGEMENT APOLLO A02 PADDLE PAGER

	Wide Band			Narrow Band		
	VHF	UHF	900	VHF	UHF	900
Frequency	138-174 MHz				408-473-MHz	9
Paging Sensitivity	512 bps – 5?V/M, 1200 bps – 2400bps - 2400bps – 9?V/M					
Bit Rate	512 / 1200 / 2400bps for POC					
Channel Spacing	25Khz					
Code Format	POCSAG					
Spurious Rejection	40db below carrier					
Alert Tone Loudness	85db @ 10 cm					
Capcodes	4 CAP codes for POCSAG					
Dimension	5.6 (L) x 20.5 (W) x 2.1 c					
Weight with Battery	Approximately 108.50 g					